



TR ART NO.	Slide length	Slide Travel	A	B	C	D	E	F	G	H	I	J	K	L	M	N
13636S00	250	250	250	30	/	/	/	/	/	160	30	233	245	160	233	172.5
13636S01	300	300	300	/	64	/	/	/	62	/	/	283	295	79	113	198
13636S02	350	350	350	/	64	150	224	30	/	288	30	333	345	128	128	249
13636S03	400	400	400	/	64	/	224	/	/	288	30	383	395	128	192	249
13636S04	450	450	450	/	64	150	224	30	/	352	30	433	445	160	192	274.5
13636S05	500	500	500	/	64	150	256	30	/	416	30	483	495	192	224	325.5
13636S06	550	550	550	/	64	150	288	30	/	448	30	533	545	224	224	351
13636S07	600	600	600	/	64	150	288	30	/	480	30	583	595	224	256	376.5
13636S08	650	650	650	/	64	150	320	30	/	544	30	633	645	256	288	402
13636S09	700	700	700	/	64	150	352	30	/	608	30	683	695	288	320	427.5

Customer part no. [ ] Dimensions within brackets are reference dimensions.

Thomas Regout Int. B.V. reserves the right to alter non-customer specific specifications without notice.

Date	Gen.Tol.Dim. ± 0.5	Third angle projection	Material	CRS-SPCC
Approver	Gen.Tol.Angle ± 0.5		Finish	Zinc Plating
Date	Gen.Roughness Ra		Draw type	Fabrication
Description	Units mm/deg.	Scale 1 : 1	Type	Model No.

TRA 3601SD ALLMAN

Formel	<b>THOMAS REGOUT INTERNATIONAL B.V.</b>	Item No.	TRA3613SD	Revision	00
A3					

© THOMAS REGOUT INTERNATIONAL B.V., Industrieweg 40, 6219 NR, Maastricht, The Netherlands, +31 (0)43 381 66 66 All rights are reserved.

NOTES:  
1. RIGHT HAND SLIDE=LEFT HAND SLIDE