



Slide number	Installation length L (inch)	Travel T (inch)	Load per pair (kg steel)	Dimension A	Dimension B	Dimension C
138150S03	11,811	11,811	1720	3,937	-	-
138150S04	13,780	13,780	1790	1,969	-	1,969
138150S05	15,748	15,748	1860	1,969	-	3,937
138150S06	17,717	17,717	1930	1,969	-	5,906
138150S07	19,685	19,685	2020	1,969	-	7,874
138150S08	21,654	21,654	2100	1,969	-	9,843
138150S09	23,622	23,622	2180	1,969	-	11,811
138150S10	25,591	25,591	2250	1,969	5,906	-
138150S11	27,559	27,559	2300	1,969	6,890	-
138150S12	29,528	29,528	2340	1,969	7,874	-
138150S13	31,496	31,496	2380	3,937	5,906	-
138150S14	33,465	33,465	2410	3,937	6,890	-
138150S15	35,433	35,433	2370	3,937	7,874	-
138150S16	37,402	37,402	2330	3,937	8,858	-
138150S17	39,370	39,370	2300	3,937	9,843	-
138150S18	41,339	41,339	2270	3,937	10,827	-
138150S19	43,307	43,307	2240	3,937	11,811	-
138150S20	45,276	45,276	2210	3,937	12,795	-
138150S21	47,244	47,244	2180	3,937	13,780	-

The load capacities are based on a 1% deflection test based on a simulation model (Finite Element Analysis)  
 Load capacity in practice always depends on mounting use and other external factors that can influence this.  
 Tolerance ±0,5mm measured from reference point.

**DIMENSIONS ARE CALCULATED FROM METRIC VALUES**  
**THOMAS REGOUT INT. BV. RESERVES THE RIGHT TO ALTER NON-CUSTOMER SPECIFICATIONS WITHOUT NOTICE**

Designer M,Urlings	Gen.Tol.Dim. ± 0.0197	Third angle projection	Material	
Date 18-7-2018	Gen.Tol.Angle ± 0.0197		Treatment	
Approver	Gen.Roughness Ra		Draw type Fabrication	Doc.No. E000149182
Date	Units inch/deg.		Scale 1 : 3	Type

Description  
**SUPREME TR15055 - (55)**

Format A2	<b>THOMAS REGOUT INTERNATIONAL B.V.</b>	Item No. 138150-Sxx	Revision 01
-----------	---	---------------------	-------------

Released for Production

© THOMAS REGOUT INTERNATIONAL BV, Industrieweg 40, 6219 NR, Maastricht, The Netherlands, +31 (0)43 351 66 66 All rights are reserved.

Rev	Date	Description	Designer
01	16-6-2023	REVISED MODEL AND TABLE.	R.G