













































custom made slides								
SINGLE EXTENSION	Junior 10 kg	Ems 30 kg	Leon 41 kg	Finn 62 kg	Ado 73 kg (bottom mount 60 kg)			
								
SINGLE EXTENSION TWO WAY Length, travel and weight are customer specific	Ems	Leon	Finn	HAS / Monte		FlexFit 1529	FlexFit 1537	
								
FULL EXTENSION	Double Ems 23 kg	Double Leon 34 kg	Double Finn 55 kg	Allman 25 kg	Sten 45 kg	Solar 90 kg	Tricom 90 kg	Ulf HD 115 kg
								
	Condor 70 kg	Jumbo 310 kg	FULL EXTENSION ALUMINIUM			Alu 40 kg	Hybrid * Double Leon 40 kg	Hybrid ** Double Leon 70 kg
								
FULL EXTENSION TWO WAY Length, travel and weight are customer specific	Bilex	LARDER UNIT		Larder Unit Wood 80-120 kg		Larder Unit Steel 80-120 kg		Larder Unit Heavy Duty 300 kg
								
SUPER HEAVY DUTY	Supra TR-7526 387 kg	Supra TR-7532 250 kg	Supra TR-8026 330 kg aluminium		Supreme 50 - 2100 kg	Supreme S-design slide 150 - 420 kg		
								
Technical specifications: Mentioned load capacities are based on 100.000 cycles. Static load capacities (10.000 cycles) available on request. Installation width per slide + 0,5 mm for optimal movement. * D. Leon Hybrid based on 20.000 cycles, length 300 - 500 mm ** D. Leon Hybrid HD based on 30.000 cycles, length 300 - 500 mm								



	telescopic slide single extension slides	technical drawing	description			load capacity			art. nr.	fixation
			length mm	travel mm		cycles 10.000	cycles 50.000	cycles 100.000		
TR - 2710 EMS 1			300	210	22 kg			17 kg	109042F	Cabinet side
			350	240	26 kg			20 kg	109043F	Metal: M4 / ISO 7380
			400	290	26 kg			20 kg	109044F	Wood: 4,0 / DIN 7997
			500	370	28 kg			22 kg	109046F	Drawer side
										Metal: M4 / DIN 965
										Wood: 3,5 / DIN 7997
TR - 2711 EMS 2			300	210	22 kg			17 kg	109049F	Cabinet side
			350	240	26 kg			20 kg	109050F	Metal: M4 / ISO 7380
			400	290	26 kg			20 kg	109051F	Wood: 4,0 / DIN 7997
			450	340	26 kg			20 kg	109052F	
			500	370	28 kg			22 kg	109053F	Drawer side
			550	420	23 kg			18 kg	109054F	Metal: M3 / DIN 7985 / ISO 7045
			600	460	23 kg			18 kg	109055F	Wood: 3,0 / DIN 7997
TR - 3714 FINN 2			300	205	78 kg			60 kg	107230F	Cabinet side
			350	239	63 kg			49 kg	107231F	Metal: M4 / DIN 7984
			400	289	54 kg			42 kg	107232F	M4 / M5 / ISO 7380
			450	339	46 kg			36 kg	107233F	Wood: 5,0 / DIN 7997
			500	373	54 kg			42 kg	107234F	
			600	457	56 kg			43 kg	107236F	Drawer side
			700	541	56 kg			43 kg	107238F	Metal: M4 / DIN 965 / ISO 7046
										M4 / DIN 7500
										Wood: 4,5 / DIN 7997
TR - 3715 FINN 3			300	205	78 kg			60 kg	107239F	Cabinet side
			350	239	63 kg			49 kg	107240F	Metal: M4 / DIN 7984
			400	289	54 kg			42 kg	107241F	M5 / DIN 7985 / ISO 7045
			450	339	46 kg			36 kg	107242F	M4 / M5 / ISO 7380
			500	373	54 kg			42 kg	107243F	Wood: 5,0 / DIN 7997
			600	457	56 kg			43 kg	107245F	
			700	541	56 kg			43 kg	107247F	Drawer side
										Metal: M3 / DIN 7985 / ISO 7045
										Wood: 3,0 / DIN 7997
TR - 3727 FINN DOUBLE			315	395	vertical mounted				117270	Cabinet side
					52 kg			40 kg		Metal: M4 / DIN 965 / ISO 7046
					horizontal mounted					M4 / DIN 7500
					32 kg			25 kg		Wood: 4,0 / DIN 7997
TR - 4522 ADO			350	224	vertical mounted				105042	Cabinet side
					91 kg			70 kg		Metal: M6 / DIN 965 / ISO 7046
					horizontal mounted					Wood: 6,0 / DIN 7997
					58 kg			45 kg		Drawer side
										Metal: M4 / DIN 965 / ISO 7046
										M4 / DIN 7500
										Wood: 4,0 / 4,5 / DIN 7997










	telescopic slide full extension slides	technical drawing	description		load capacity		art. nr.	fixation
			length mm	travel mm	cycles 10.000	cycles 100.000		
TR - 5513 Solar S			350	332	45 kg	38 kg	103R92F*	Cabinet side
			400	400	55 kg	45 kg	103R93F	Metal: M5 / DIN 965
			450	450	60 kg	60 kg	103R94F*	Wood: 5,0 / DIN 7997
			500	505	60 kg	60 kg	103R95F	Drawer side
								Metal: M4 / DIN 965
TR - 5617 ULF HD B			300	320	94 kg	68 kg	112S01F	Cabinet side
			350	375	96 kg	77 kg	112S02F	Metal: M5 / DIN 965 / ISO 7046
			400	440	97 kg	73 kg	112S03F	M5 / DIN 7500
			450	495	110 kg	83 kg	112S04F	Wood: 5,0 / DIN 7997
			500	550	119 kg	90 kg	112S05F	Drawer side
TR - 5617 ULF HD D			300	320	94 kg	68 kg	112S21F	Cabinet side
			350	375	96 kg	77 kg	112S22F	Metal: M5 / DIN 965 / ISO 7046
			400	440	97 kg	73 kg	112S23F	M5 / DIN 7500
			450	495	110 kg	83 kg	112S24F	Wood: 5,0 / DIN 7997
			500	550	119 kg	90 kg	112S25F	Drawer side
TR - 5620 ULF HD E			300	285	94 kg	64 kg	112S41F	Cabinet side
			350	350	96 kg	73 kg	112S42F	Metal: M5 / DIN 965 / ISO 7046
			400	400	97 kg	77 kg	112S43F	M5 / DIN 7500
			450	450	110 kg	88 kg	112S44F	M5 / DIN 7991 / ISO 10462
			500	500	119 kg	90 kg	112S45F	Wood: 5,0 / DIN 7997
TR - 5618 ULF HD F			300	285	94 kg	64 kg	112S61F	Cabinet side
			350	350	96 kg	73 kg	112S62F	Metal: M5 / DIN 965 / ISO 7046
			400	400	97 kg	77 kg	112S63F	M5 / DIN 7500
			450	450	110 kg	88 kg	112S64F	M5 / DIN 7991 / ISO 10462
			500	500	119 kg	90 kg	112S65F	Wood: 5,0 / DIN 7997
TR - 5618 ULF HD BILEX			500	503 - 503	114 kg	76 kg	112S11F	Cabinet side
			600	607 - 607	119 kg	79 kg	112S10F	Metal: M5 / DIN 965 / ISO 7046
			700	711 - 711	131 kg	87 kg	112S09F	M5 / DIN 7500
			800	815 - 815	138 kg	92 kg	112S12F	Wood: 5,0 / DIN 7997
								Drawer side
TR - 5619 ULF HD S			350	335	65 kg	57 kg	112S82F	Cabinet side
			400	400	75 kg	68 kg	112S83F	Metal: M5 / DIN 965 / ISO 7046
			450	451	75 kg	75 kg	112S84F	M5 / DIN 7500
			500	506	75 kg	75 kg	112S85F	M5 / DIN 7991 / ISO 10462
			550	555	75 kg	75 kg	112S86F	Wood: 5,0 / DIN 7997

* min. of 250 pair, lead time on request

standard program




telescopic slides

	telescopic slide full extension slides	technical drawing	description		load capacity			art. nr.	fixation				
			length mm	travel mm	cycles 10.000	cycles 50.000	cycles 100.000						
TR - 7120 TITAN B	 Drawer Carrier Bumper with hold closed		400	435	157 kg		97 kg	101S03F	Cabinet side				
			450	485	160 kg		103 kg	101S04F	Metal: M5 / DIN 965 / ISO 7046				
			500	545	169 kg		115 kg	101S05F	M5 / DIN 7500				
			550	595	187 kg		118 kg	101S06F	Wood: 5,0 / DIN 7997				
			600	650	189 kg		118 kg	101S07F	Drawer side				
			700	750	187 kg		137 kg	101S08F	Metal: M3 / DIN 7985 / ISO 7045				
										Wood: 3,0 / DIN 7997			
TR - 7118 TITAN D	 Bumper with hold closed		400	435	157 kg		97 kg	101S23F	Cabinet side				
			450	485	160 kg		103 kg	101S24F	Metal: M5 / DIN 965 / ISO 7046				
			500	545	169 kg		115 kg	101S25F	M5 / DIN 7500				
			550	595	187 kg		118 kg	101S26F	Wood: 5,0 / DIN 7997				
			600	650	189 kg		118 kg	101S27F	Drawer side				
			700	750	187 kg		137 kg	101S28F	Metal: M4 / DIN 965 / ISO 7046				
			800	850	212 kg		147 kg	101S29F	M4 / DIN 7500				
			900	950	192 kg		125 kg	101S30F	Wood: 4,0 / 4,5 / DIN 7997				
			1000	1050	179 kg		108 kg	101S31F					
TR - 7120 TITAN E	 Drawer Carrier Pull in with fail-safe		400	400	170 kg		103 kg	101S43F	Cabinet side				
			450	450	190 kg		116 kg	101S44F	Metal: M5 / DIN 965 / ISO 7046				
			500	500	212 kg		125 kg	101S45F	M5 / DIN 7500				
			550	550	230 kg		140 kg	101S46F	Wood: 5,0 / DIN 7997				
			600	600	230 kg		145 kg	101S47F	Drawer side				
			700	700	228 kg		145 kg	101S48F	Metal: M3 / DIN 7985 / ISO 7045				
			800	800	219 kg		155 kg	101S49F	Wood: 3,0 / DIN 7997				
TR - 7118 TITAN F	 Pull in with fail-safe		400	400	170 kg		103 kg	101S63F	Cabinet side				
			450	450	190 kg		116 kg	101S64F	Metal: M5 / DIN 965 / ISO 7046				
			500	500	212 kg		125 kg	101S65F	M5 / DIN 7500				
			550	550	230 kg		140 kg	101S66F	Wood: 5,0 / DIN 7997				
			600	600	230 kg		145 kg	101S67F	Drawer side				
			700	700	228 kg		145 kg	101S68F	Metal: M4 / DIN 965 / ISO 7046				
			800	800	219 kg		155 kg	101S69F	M4 / DIN 7500				
									Wood: 4,0 / 4,5 / DIN 7997				
TR - 7125 CONDOR	 Bumper with hold closed		300	395	80 kg			111M32F	Cabinet side				
			400	595	90 kg			111M33F	Metal: M5 / DIN 965 / ISO 7046				
			500	750	90 kg			111M34F	M5 / DIN 7500				
			600	900	100 kg			111M35F	Wood: 5,0 / DIN 7997				
			700	1050	100 kg			111M36F	Drawer side				
			800	1200	100 kg			111M37F	Metal: M4 / DIN 965 / ISO 7046				
			900	1350	100 kg			111M38F	M4 / DIN 7500				
									M4 / DIN 7991 / ISO 10462				
									Wood: 4,0 / 4,5 / DIN 7997				
TR - 7619 JUMBO	 Bumper without hold closed Lock in / Lock out		descript.	load capacity		art. nr. ***			fixation				
			L mm	T mm	cycles 10.000	cycles 50.000		with lock in left slide	with lock in right slide	with lock out	with lock in left slide	with lock in right slide	
			300	298	225 kg	195 kg	114S31	AL	AR	B	DL	DR	Cabinet side
			350	366	235 kg	200 kg	114S32	AL	AR	B	DL	DR	Metal: M5 / DIN 7984
			400	398	250 kg	210 kg	114S33	AL	AR	B	DL	DR	M5 / M6 / ISO 7380
			450	464	255 kg	220 kg	114S34	AL	AR	B	DL	DR	
			500	512	260 kg	230 kg	114S35	AL	AR	B	DL	DR	Drawer side
			550	562	265 kg	240 kg	114S36	AL	AR	B	DL	DR	Metal: M5 / DIN 7984
			600	610	275 kg	255 kg	114S37	AL	AR	B	DL	DR	M5 / M6 / ISO 7380
			650	660	285 kg	265 kg	114S46	AL	AR	B	DL	DR	
			700	708	295 kg	280 kg	114S38	AL	AR	B	DL	DR	
			750	758	300 kg	290 kg	114S47	AL	AR	B	DL	DR	
			800	806	310 kg	300 kg	114S39	AL	AR	B	DL	DR	
			850	854	315 kg	300 kg	114S43	AL	AR	B	DL	DR	
			900	904	320 kg	310 kg	114S40	AL	AR	B	DL	DR	
			1000	1000	325 kg	315 kg	114S41	AL	AR	B	DL	DR	
			1100	1098	305 kg	290 kg	114S44	AL	AR	B	DL	DR	
			1200	1212	295 kg	280 kg	114S42	AL	AR	B	DL	DR	
			1350	1358	245 kg	210 kg	114S48	AL	AR	B	DL	DR	
			1500	1504	225 kg	195 kg	114S45	AL	AR	B	DL	DR	






*** Add AL behind article number for "with lock in" on the left slide or AR for on the right slide.
Add B behind article number for "with lock out".
Add DL behind article number for "with lock in/out, front release" on the left slide or DR for on the right slide.

standard program

larder units and linear guides







	larder units full extension slides	technical drawing	descript.	load cap.	art. nr.		art. nr.		art. nr.		art. nr.			
			L mm	T mm	cycles 10.000		L mm	T mm		T mm		L mm	T mm	
Larder Unit for Wood			bottom slide TITAN			top slide FINN roller			top slide U-guide		top slide ULF HD pin			
			425	425	80 - 120 kg	150A67	412	289	127A10	425	1556441	403	455	124B63
			485	485	80 - 120 kg	150A68	465	312	127A08	480	1556438	458	510	124B47
			585	585	80 - 120 kg	150A69	465	312	127A08	580	1556439	556	610	124B64
			750	750	80 - 120 kg	150A70	675	424	127A09	750	1556440	721	780	124B65
			optional bracket set			1539954								
Larder Unit for Steel			bottom slide TITAN KIT inclusive			top slide ULF HD pin			optional top slide FINN roller					
			485	485	80 - 120 kg	150A71	403	455				412	289	127A10
			585	580	80 - 120 kg	150A72	458	510				465	312	127A08
Larder Unit for Heavy duty			bottom slide JUMBO KIT inclusive			top slide ULF HD pin								
			650	650	300 kg	150A38								

please visit our website www.thomasregout.com for more customized solutions







	linear guides	technical drawing	description		load cap.	art. nr.	fixation	
			length mm	travel mm	cycles 60.000 (1 meter per cycle)			
FlexFit - 1537			3 wheel carrier			Rad. 800N	Cabinet side	
			5 wheel carrier			Rad. 1150N	Metal: M5 - 8.8 / DIN 7991 / ISO 10463	
			Profile - galvanised steel	max 2394**	depending on length	on request	Wood: 5,0 / DIN 7997	
			Profile - stainless steel	max 3994**	depending on length	on request	Drawer side	
							Metal: M5 / DIN 965 / ISO 7046 M5 / DIN 7500	
				weight 20 gram		16901223		
FlexFit - 1529			3 wheel carrier			Rad. 425N	Cabinet side	
			5 wheel carrier			Rad. 650N	Metal: M5 - 8.8 / DIN 7991 / ISO 10462	
			Profile - galvanised steel	max 2394**	depending on length	on request	Wood: 5,0 / DIN 7997	
			Profile - stainless steel	max 3994**	depending on length	on request	Drawer side	
							Metal: M5 / DIN 965 / ISO 7046 M5 / DIN 7500	
				weight 20 gram		16901223		
FlexFit Rubber Stop			Rubber Stop 1537	37x12,8x30			205S118	packed per pair
			Rubber Stop 1529	29x12,8x30			205S128	packed per pair

** customer specific available in all lengths



	heavy duty full extension slides	technical drawing	description		load capacity cycles 10.000	art. nr.	fixation
			length mm	travel mm			
TR - 7532 SUPRA			300	450	150 kg	13875S61	Cabinet side
			350	525	184 kg	13875S62	Metal: M5 / DIN 7991 / ISO 10462
			400	600	212 kg	13875S63	
			450	675	224 kg	13875S64	Drawer side
			500	750	232 kg	13875S65	Metal: M6 / DIN 7991 / ISO 10462
			550	825	240 kg	13875S66	
			600	900	250 kg	13875S67	
			650	975	235 kg	13875S68	
			700	1050	220 kg	13875S69	
			750	1125	200 kg	13875S70	
			800	1200	180 kg	13875S71	
			850	1275	160 kg	13875S72	
			900	1350	140 kg	13875S73	
			950	1425	120 kg	13875S74	
			1000	1500	100 kg	13875S75	
TR - 7526 - 100 SUPRA	100% Extension 		300	310	360 kg	13875S01	Cabinet side
			350	360	380 kg	13875S02	Metal: M5 / DIN 7991 / ISO 10462
			400	410	390 kg	13875S03	
			450	460	400 kg	13875S04	Drawer side
			500	510	410 kg	13875S05	Metal: M8 / DIN 7991 / ISO 10462
			550	560	420 kg	13875S06	
			600	610	430 kg	13875S07	
			650	660	420 kg	13875S08	
			700	710	410 kg	13875S09	
			750	760	400 kg	13875S10	
			800	810	390 kg	13875S11	
			850	860	380 kg	13875S12	
			900	910	370 kg	13875S13	
			950	960	360 kg	13875S14	
			1000	1010	350 kg	13875S15	
TR - 7526 - 120 SUPRA	120% Extension 		300	360	324 kg	13875S31	Cabinet side
			350	420	342 kg	13875S32	Metal: M5 / DIN 7991 / ISO 10462
			400	480	351 kg	13875S33	
			450	540	360 kg	13875S34	Drawer side
			500	600	396 kg	13875S35	Metal: M8 / DIN 7991 / ISO 10462
			550	660	378 kg	13875S36	
			600	720	387 kg	13875S37	
			650	780	378 kg	13875S38	
			700	840	369 kg	13875S39	
			750	900	360 kg	13875S40	
			800	960	350 kg	13875S41	
			850	1030	342 kg	13875S42	
			900	1080	333 kg	13875S43	
			950	1140	324 kg	13875S44	
			1000	1200	315 kg	13875S45	
TR - 8026 ALU SUPRA			300	285	250 kg	13880S01	Cabinet side
			350	335	260 kg	13880S02	Metal: M5 / DIN 7991 / ISO 10462
			400	385	270 kg	13880S03	
			450	435	280 kg	13880S04	Drawer side
			500	485	300 kg	13880S05	Metal: M8 / DIN 7991 / ISO 10462
			550	535	320 kg	13880S06	
			600	585	330 kg	13880S07	
			650	635	315 kg	13880S08	
			700	685	300 kg	13880S09	
			750	735	290 kg	13880S10	
			800	785	280 kg	13880S11	
			850	835	270 kg	13880S12	
			900	885	260 kg	13880S13	
			950	935	250 kg	13880S14	
			1000	985	240 kg	13880S15	
SUPREME	 • Steel • Aluminium • Stainless steel 		length / extension 200 - 1200 mm load capacity 50 - 2100 kg				
			More information; check our complete Supreme program on www.thomasregout.com or ask our sales team.				
SUPREME S-design slide	 		length / extension 200 - 1200 mm load capacity 150 - 420 kg				
			More information; check our complete Supreme program on www.thomasregout.com or ask our sales team.				



	telescopic slide full extension slides	technical drawing	description		load capacity			art. nr.	fixation
			length mm	travel mm	cycles 10.000	cycles 50.000	cycles 100.000		
TRA - 1710 JUNIOR			178	129	8 kg	5 kg		13617S07	screw mount
			182	133	8 kg	5 kg		13617S08	screw mount
			214	140	8 kg	5 kg		13617S09	screw mount
			246	172	11 kg	8 kg		13617S01	screw mount
			278	204	11 kg	8 kg		13617S10	screw mount
			310	212	13 kg	10 kg		13617S02	screw mount
			342	244	13 kg	10 kg		13617S03	screw mount
			374	276	11 kg	8 kg		13617S11	screw mount
			406	308	11 kg	8 kg		13617S04	screw mount
			438	318	10 kg	7 kg		13617S05	screw mount
			470	350	8 kg	5 kg		13617S12	screw mount
			502	382	8 kg	5 kg		13617S06	screw mount
TRA - 3613SD ALLMAN	 Bumper hold in Trigger release disconnect		250	250	20 kg	18 kg	15 kg	13636S00	Cabinet side
			300	300	20 kg	18 kg	15 kg	13636S01	Metal: M3 / M4 / ISO 7380
			350	350	22 kg	20 kg	18 kg	13636S02	Wood: 2,9 / DIN 7981 / ISO 7049
			400	400	25 kg	22 kg	20 kg	13636S03	
			450	450	25 kg	22 kg	20 kg	13636S04	Drawer side:
			500	500	22 kg	20 kg	18 kg	13636S05	Metal: M3 / DIN 7984
			550	550	22 kg	20 kg	18 kg	13636S06	M3 / DIN 7985 / ISO 7045
			600	600	20 kg	18 kg	15 kg	13636S07	M4 / ISO 7380
			650	650	20 kg	18 kg	15 kg	13636S08	Wood: 2,9 / DIN 7981 / ISO 7049
			700	700	20 kg	18 kg	15 kg	13636S09	
TRA - 4613SD STEN	 Bumper hold in Trigger release disconnect		250	250	45 kg	38 kg	32 kg	13645S20	Cabinet side
			300	300	46 kg	40 kg	34 kg	13645S21	Metal: M4 / DIN 7984
			350	350	48 kg	42 kg	36 kg	13645S22	M3 / DIN 7985 / ISO 7045
			400	400	51 kg	45 kg	39 kg	13645S23	M4 / ISO 7380
			450	450	51 kg	45 kg	39 kg	13645S24	Wood: 3,5 / DIN 7981 / ISO 7049
			500	500	48 kg	42 kg	36 kg	13645S25	
			550	550	46 kg	40 kg	34 kg	13645S26	Drawer side
			600	600	44 kg	40 kg	34 kg	13645S27	Metal: M4 / ISO 7380
			650	650	42 kg	38 kg	32 kg	13645S28	Wood: 3,5 / DIN 7981 / ISO 7049
			700	700	42 kg	38 kg	32 kg	13645S29	
			750	750	40 kg	36 kg	30 kg	13645S30	
			800	800	40 kg	36 kg	30 kg	13645S31	
TRA - 4613CL STEN	 Self-close, Trigger release disconnect		300	300	33 kg	30 kg	24 kg	13645S41	Cabinet side
			350	350	38 kg	35 kg	29 kg	13645S42	Metal: M4 / DIN 7984
			400	400	43 kg	40 kg	34 kg	13645S43	M3 / DIN 7985 / ISO 7045
			450	450	43 kg	40 kg	34 kg	13645S44	M4 / ISO 7380
			500	500	38 kg	35 kg	29 kg	13645S45	Wood: 3,5 / DIN 7981 / ISO 7049
			550	550	33 kg	30 kg	24 kg	13645S46	
			600	600	32 kg	30 kg	24 kg	13645S47	Drawer side
			650	650	30 kg	28 kg	22 kg	13645S48	Metal: M3 / DIN 7984
			700	700	30 kg	28 kg	22 kg	13645S49	M3 / DIN 7985 / ISO 7045
									M4 / ISO 7380
									Wood: 2,9 / DIN 7981 / ISO 7049
TRA - 4613SMC STEN	 Soft close, Trigger release disconnect		300	250	26 kg	20 kg	14 kg	13645S61	Cabinet side
			350	320	26 kg	20 kg	14 kg	13645S62	Metal: M4 / DIN 7984
			400	375	31 kg	25 kg	19 kg	13645S63	M3 / DIN 7985 / ISO 7045
			450	450	36 kg	30 kg	24 kg	13645S64	M4 / ISO 7380
			500	500	36 kg	30 kg	24 kg	13645S65	Wood: 3,5 / DIN 7981 / ISO 7049
			550	550	31 kg	25 kg	19 kg	13645S66	
			600	600	31 kg	25 kg	19 kg	13645S67	Drawer side
			650	650	26 kg	20 kg	14 kg	13645S68	Metal: M3 / DIN 7984
									M3 / DIN 7985 / ISO 7045
									M4 / ISO 7380
									Wood: 2,9 / DIN 7981 / ISO 7049
TRA - 4613PO STEN	 Push to open, Trigger release disconnect		350	350	38 kg	35 kg	29 kg	13645S82	Cabinet side
			400	400	43 kg	40 kg	34 kg	13645S83	Metal: M4 / DIN 7984
			450	450	43 kg	40 kg	34 kg	13645S84	M3 / DIN 7985 / ISO 7045
			500	500	38 kg	35 kg	29 kg	13645S85	M4 / ISO 7380
			550	550	33 kg	30 kg	24 kg	13645S86	Wood: 3,5 / DIN 7981 / ISO 7049
			600	600	30 kg	24 kg	20 kg	13645S87	
			650	650	30 kg	24 kg	20 kg	13645S88	Drawer side
									Metal: M3 / DIN 7984
									M3 / DIN 7985 / ISO 7045
									M4 / ISO 7380
									Wood: 2,9 / DIN 7981 / ISO 7049



features, fixations, systems and surface treatments

FEATURES	Bumper without hold closed	Bumper with hold closed	Hold out	Hold out disconnection inner profile	Lock out disconnection inner profile	Lock in / horizontal latch front release	Lock in / vertical latch front release	Soft close damper integrated	Soft close damper outside
									
	Pull in 30N 22mm	Pull in 42N 35mm	Pull in 54N 22mm	Electric Discharging	Push to open				
									
FIXATIONS	Holes	Countersunk holes	Press inserts	Studs	Studs threaded	Tabs / Bajonets	Slotted strip bracket	Spacer bracket	Drawer carrier
							 spotwelded	 spotwelded	 spotwelded
SYSTEMS	Larder Unit	ISL Integrated slide lock	ISL lock	Rack and Pinion	UDL				
									
SURFACE TREATMENTS									
	- Bright zinc chromate, black passivation, up to 120 hours (white corrosion), organic / inorganic leachant sealant NEN EN-ISO 9227 / ASTM-B117) - Bright zinc chromate, blue passivation up to 96 hours (white corrosion), organic / inorganic leachant sealant NEN EN-ISO 9227 / ASTM-B117) - Pre- galvanized (Sendzimir)								

